Water Tight Tankage Spec. AdvanTex ™Treatment System - 1 tank Design For Enhanced It Is Necessary That Tanks Enhanced Nitrogen Reduction Be Vacuum Or Water Tested AX 20 Series - Mode 3a To Certify Water Tight Tankage. PVC Acces Risers Must Be Water Tight, Epoxied To Tankage And Bolted Down For Liability Consideration. Contractor/Tank Manufacturer Shall Be Responsible Orenco Systems ® For Repair Or Replacement Of Tanks With Leaks or Defects. Tankage Must Have 3 Year Warranty. -0-0-0-0-0-0-0-0-0-0-0-0-0-0-0 2" Filtrate Return Line 0-0-0-0-0-0-0-0-0-0-0-0-0-0 AdvanTex Filter-2" Discharge Filtrate -1" Forcemain Inlet → 5 Top View AdvanTex Filter -2" Dia. Vent Inlet Riser/Lid-Recirculating Splitter Valve (RSV) With 24" Dia. Riser Quick Disconnect 36" Slope (min. 1/4"/ft.) 5<u>" Minimum</u> Discharge Filtrate Inlet →2 20" Dia Opening 2 Compartment Tank 68" Pump Vault 1000 Gallon 500 Gallon -Biotube® Pump Package 1500 Gallon Side View Note: Advantex and Piping must not settle Patents # 4,439,323 & 5,492,635 Orenco Systems, Inc. AX 20 Gravity (1 Tank)

DRAWING A13	HS	NO	REVISON	DATE	BY	7125 East Pickard Road	DRAWN jolu
ing no.	E		. #1	10/15	15/07	P. O. Box 309	SCALE
	유 	3.				Mt. Pleasant, MI 48804-0309 ph-989-773-9938	date 9/30/03
	_	5.				Systems fax-989-772-3415	APPROVED